



High-Performance Subsea Gyrocompass & Motion Sensor

OCTANS 3000 is a subsea survey-grade gyrocompass and complete motion sensor for water depths up to 3,000 m. Based on iXBlue's FOG technology it outputs heading, roll, pitch, heave, rate of turn and acceleration. OCTANS 3000 can be easily upgraded to full INS mode (i.e. ROVINS).

ROV & offshore survey, multibeam and sonar motion reference, dredging, marine construction

Key Features

- Complete gyrocompass and motion sensor
- Smart Heave™
- Fiber Optic Gyroscope (FOG), unique strapdown technology
- Ethernet, Web-based Man-Machine Interface (MMI)
- Titanium made, small, portable plug and play system
- Optional full featured Inertial Navigation System

Benefits

- High-performance real-time outputs of true heading, roll, pitch, heave, surge, sway, acceleration and rate of turn
- No spinning element hence maintenance free
- Lightweight corrosion free housing for water depth up to 3,000 m, easy to integrate and interface, saves valuable mobilisation time
- Obtain INS-class system with simple software upgrade

Specifications- performance

Heading

Accuracy (1)(2)	0.1 deg secant latitude
Resolution	0.01 deg
Full accuracy settling time (all conditions)	< 5 min
Heave accuracy (3)	2,5 cm or 2,5% (whichever is greater)
Roll / Pitch	0.01 deg
Dynamic accuracy (2)	0.001 deg

Operating Range / Environment

Operating / Storage Temperature	-20 to +55°C/ -40 to +80 °C
Follow-up speed	Up to 750 deg/s
Acceleration dynamic range	±15 g
Heading / Roll / Pitch	5 cm or 5% (whichever is greater)
MTBF (computed/observed)	0 to +360 deg / ±180 deg / ±90 deg 40,000 hours / 80,000 hours
No warm-up effects, insensitive to thermal shocks	
Shock and vibration proof	

Physical Characteristics

Depth rating	3,000 m
--------------	---------

Material	Titanium
Weight in air/water	15/6,2
Dimensions	213 x 375
Connector	5 x SEACON MI-CON
Mounting	6 Ø 6,6 holes

Interface

Serial RS232/RS422 port	5 inputs / 5 outputs / 1 configuration port
Ethernet port (5)	UDP / TCP Client / TCP server
Pulse port (6)	3 inputs / 2 outputs
Sensors supported	GPS, Speed log
Input/Output formats	Industry standards: NMEA0183, ASCII, BINARY
Baud rates	600 bauds to 115.2 kbaud
Data output rate	0.1 Hz to 200 Hz
Power supply	24 VDC
Power consumption	< 20 W

(1) secant latitude = $1 / \cosine \text{ latitude}$

(2) RMS values

(3) Smart Heave™

(4) All input /output serial ports are available and can be duplicated on Ethernet ports

(5) Input of GPS PPS pulse for accurate time synchronization of OCTANS 3000

Specifications subject to change without notice