

## Super ZipJet Excavation & Jetting System - 25 h.p.

### Features

- Improved performance
- Much improved ROV mounting system
- Modular pump core, readily removable for easier in-field maintenance
- Suction and jetting aligned for ease of hose management
- Multiple mounting and handling configurations
- The integrated eductor based excavation system is designed to pump mud, sand, gravel, drill cuttings, shale etc. without damage to the system and with a very low risk of blockage

### Applications

- The Super ZipJet is so compact that it may be mounted on most work class ROVs without the need for an additional dredging skid
- Break up of heavy and cohesive sea-bed muds and sand prior to excavation
- Removal of drill cuttings
- Deburial of subsea templates and manifolds
- Removal of marine growth prior to inspection
- Marine archaeology
- Salvage operations




The all-new Super ZipJet replaces the successful Tritech ZipJet Ultra range of products.

The Super ZipJet incorporates many technical advances over the previous generation of ROV suction and jetting systems. These advances are a direct result of customer feedback.

Considerable emphasis has been placed on increasing efficiency in both the suction and jetting modes. The Super ZipJet incorporates several design features which improve its reliability and substantially reduce its maintenance costs.

The Super ZipJet will not block or jam because there are no moving parts on the dredging side of the system. Power is derived from a stream of high velocity fluid creating a low pressure region behind the suction nozzle. The pump may be rapidly switched from suction to jetting mode.

## Specifications



### Hydraulic Input

**Pressure** 150 to 220 Bar 2200 to 3200 psi

**Flow** 40 to 60 litres / min 11 to 16 USgpm

**Jetting Performance (Typical)** 500 litres / min @ 4 Bar (130 USgpm)

**Suction Performance (Typical)**  
**Suction Flow (Typical)** 500 - 1000 litres / min (135 - 270 USgpm)

**Solids Removal Rate** 5 - 10 tonnes / hour (5 - 10 tons / hour)

### Nozzle and Hose Dimensions

**Jetting Hose** 25mm ID 1 inch

**Jet Nozzle Diameter** 20 mm 0.8 inches

**Discharge Hose Diameter** 100 mm ID 4 inches

**Suction Hose Diameter** 75 mm ID 3 inches

### Weights and Materials

**Weight in Air** 25 kg 55 lb

**Weight in Water** 11 kg 24 lb

**Materials** Nylacast, UHMWPE

All specifications are subject to change in line with Tritech's policy of continual product development.

Ref: EDS-HYD-001.5