



**PRODUCT DATA SHEET**

<b>PRODUCT:</b>	FLUID INJECTION SKID
<b>DESCRIPTION:</b>	FLUID INJECTION SKID 7500 PSI

**MAIN FEATURES:**

- ✓ FLUID INJECTION SKID 7500 PSI
- ✓ SIMPLE AND RELIABLE DESIGN
- ✓ LOW MAINTENANCE ALUMINUM DESIGN
- ✓ HIGH PRESSURE PUMP – DYNASET
- ✓ OPERATED BY STANDARD WORKING ROV FOR SUBSEA APPLICATIONS
- ✓ INTEGRATED OVERLOAD VALVES ON PUMP
- ✓ CAN BE USED DOWN TO 2000 MSW
- ✓ SUPPLIED WITH FULL DOCUMENTATION AND INSTRUCTIONS
- ✓ SPECIAL DESIGNS AVAILABLE ON REQUEST
- ✓ PRESSURE GAUGE AND VALVES FOR CYLINDER OPERATION AND PRESSURE TESTING
- ✓ PRESET FOR FLUID INJECTION THROUGH HOT STAB SYSTEM





DESIGN SPECIFICATION FLUID INJECTION SKID				
MODELS COVERED - ARTICLE NO'S:				
TECHNICAL CHARACTERISTICS	UNIT	MODEL VALUES	TECHNICAL CHARACTERISTICS	MATERIAL
HEIGHT	MM	480	<b>MATERIALS</b>	
WIDTH	MM	1300	FLUID SKID FRAME	ALU 6082-T6
LENGTH	MM	3000	BUOYANCY ELEMENTS	BUOANCY, YELLOW
WEIGHT DRY EMPTY	KG	500	FLUID TANK	PVC, YELLOW
WEIGHT SUBMERGED	KG	TBA	HYDRAULICS COMPONENTS	S316
FLUID TANK CAPACITY	L	158	HIGH PRESSURE PUMP	ALU. BRONZE
OPERATIONAL DEPTH	MSW	2000		
MAX. HYDR. OPER. PRESSURE	BAR	210		
MAX. OUTPUT PRESSURE	PSI	7800		

CONNECTIONS:

- 200 BAR LINE: JIC 06
- 7500 PSI LINE: JIC 06
- TANK FILLING AND AERATION: SNAP TITE 3/4"
- PILOT LINES A AND B: JIC 04
- PUMP P AND T: JIC 12
- PUMP PRESSURE COMP.: CHECK VALVE
- COMPENSATOR: SNAP TITE
- COMPENSATOR FILLING: SNAP TITE

