

# NORTEK DVL1000 - 4000m

## DOPPLER VELOCITY LOG



Bottom-track from over 0.2 to 75 m range  $\varnothing$  400 m max. operational depth.  
The DVL1000 is the world's smallest commercially available Doppler Velocity Log. It combines compact design with unprecedented functionality, being able to fly higher in the water column and closer to the seabed than similar equipment. It has a maximum operational depth of 4000 m and is ideally suited for subsea navigation where size and weight are a concern. This 1 MHz Doppler Velocity Log is used by industry leaders in the subsea market because of its high accuracy and state-of-the-art technology.

### Key Features

Industry's smallest DVL  
Bottom track from 0.2-75 m range  
Quality estimates - per beam and ping

### Main Body

Height	164 mm
Diameter	$\varnothing$ 114 mm

### Hardware

Frequency of operation	1 MHz
Beam width	2.9°
Configuration	4.beam Janus array convex transducer, 25° beam angle
Internal memory	16 GB / 64 GB optional

## Bottom Velocity

Single ping std @ 3 m/s	0.5 cm/s
Long-term accuracy	±0.1% / ±0.1 cm/s
Minimum altitude	0.2 m
Maximum altitude	75 m
Velocity resolution	0.01 mm/s
Maximum ping rate	8 Hz max

## Water Tracking

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Minimum range	2.0 m

## Current Profiling

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Velocity resolution	0.1 cm/s
Interval	User-specific Nth ping
Maximum range	30 m
Blanking	0.1 m
Cell size	0.2-2.0 m
Max # cells	150

## Environmental

Operating temperature	-4 to +40 °C
Storage temperature	-20 to +60°C

## Mechanical

Depth rating	4000 m
Weight	2.7 kg
Weight in water	1.7 kg

## Interfaces

Serial (either serial or ethernet)	Configurable RS232 or RS422 Subconn connector, 8-pin male
Ethernet	10/100 Mbits Auto MDI-X.TCP/IP, UDP/IP, HTTP protocols. Fixed IP / DHCP client /Auto IP address assignment. UPnP and Nortek proprietary instrument discovery over Ethernet. IEEE1588/PTP and NTP for absolute time stamping.Multiple simultaneous data format transmission possible.
Data formats	Nortek proprietary w/ 1 ms time stamp accuracy, NMEA0183, Variants of PDx
Trigger	Internal 1, 2, 3, 4, 5, 6, 7 or 8 Hz or Trigger In. Trigger option through command (Ethernet or serial) External TTL or 485 lines: (configurable Rising/Falling/Edges)

## Sensors

Pressure	0.1% FS /precision better than 0.002% of full scale per sample
Temperature	-4° to +40 °C ± 0.1 °C

## Power

DC input	12-48 V
Maximum peak current	1.5 A
Average power	1.3 W

## Materials

Standard models	POM and titanium housing
-----------------	--------------------------