SubseaHooks™

Manufactured by Nautilus Rigging LLP

Technically advanced design with patented “positive locking” function sets new standard for safe, secure subsea lifting. Nautilus ROV hooks incorporate patented locking technology with unique “Positive Locking” function, ensuring load integrity in the subsea environment. Innovative and cost effective, Nautilus subsea hooks eliminate the risk of load self-release, ensuring safe and secure subsea lifting operations.

Key Features

Unique “positive locking” function eliminates risk of self release
Outward opening locking arm eliminates “slings” fouling behind latch
Self locking under load – load remains
securely locked until released by ROV
Nautilus subsea hooks are manufactured to EU standard BS/EN 1677-1+A1/2008
Individually proof tested to 2.5 x working load limit
4:1 safety factor – working load limit 22 tonnes
Nautilus ROV Hooks are fatigue rated to 20,000 cycles at 1.5 x the working load limit.
Supplied with manufacturer’s test certification
Patented Nautilus Design - USA Patent Number US 8,240,727 B2

Nautilus ROV & Subsea Hooks

Component	Model / Part No	WLL	Weight	L	W	H
Long Shank ROV Hook	NH-ROV22E	22 te	21.0 kg	684	264	62
Primary Activation Wire	NH-PW200	1200 kg	Bespoke 316 SS stud / wire assembly			
Secondary Activation Wire	NH-SW230	900 kg	230mm x 3mm SS wire and ferules			

Norwegian Offshore Rental AS | PO Box 2143, 5504 Haugesund | Stoltenberggata 1, 5527 Haugesund | +47 915 50 054 | post@offshorerental.no | **offshorerental.no**