

SubseaHooks™

Manufactured by Nautilus Rigging LLP

nor Offshore
Rental



Technically advanced design with patented “positive locking” function sets a new standard for safe, secure subsea lifting. Nautilus ROV hooks incorporate patented locking technology with unique “Positive Locking” function, ensuring load integrity in the subsea environment. Innovative and cost effective, Nautilus subsea hooks eliminate the risk of load self-release, ensuring safe and secure subsea lifting operations.

Key Features

- Unique “positive locking” function eliminates risk of self release
- Outward opening locking arm eliminates “slings” fouling behind latch
- Self locking under load – load remains securely locked until released by ROV
- Nautilus subsea hooks are manufactured to EU standard BS/EN 1677-1+A1/2008
- Individually proof tested to 2.5 x working load limit
- 4:1 safety factor – working load limit 22 tonnes
- Nautilus ROV Hooks are fatigue rated to 20,000 cycles at 1.5 x the working load limit.
- Supplied with manufacturer’s test certification
- Patented Nautilus Design - USA Patent Number US 8,240,727 B2

Nautilus ROV & Subsea Hooks

Component	Model / Part No	WLL	Weight	L	W	H
Long Shank ROV Hook	NH-ROV22E	22 te	21.0 kg	684	264	62
Primary Activation Wire	NH-PW200	1200 kg		Bespoke 316 SS stud / wire assembly		
Secondary Activation Wire	NH-SW230	900 kg		230mm x 3mm SS wire and ferrules		